

Zekeringen Ex eb mb Fuses Ex eb mb

Technische informatie:

Ex markering: II 2G Ex eb mb IIC T6 Gb
 II 2D Ex tb IIIC IP66 Db

Geschikt voor zone 1, 2, 21 en 22

Omgevingstemperatuur: $-20^{\circ}\text{C} \leq T_a \leq 60^{\circ}\text{C}$

Spanning: 250 V

Beschermingsgraad: IP20

Railmontage : DIN-EN montage rail TS35 en TS15

Conform de standaards: EN60079

Technical data:

Ex mark: II 2G Ex eb mb IIC T6 Gb

II 2D Ex tb IIIC IP66 Db

Can be used in zone 1, 2, 21 and 22

Ambient temperature: $-20^{\circ}\text{C} \leq T_a \leq 60^{\circ}\text{C}$

Voltage: 250 V

Degree of protection: IP20

Base mount: DIN-EN mounting rail TS35 and TS15

Meets the standards: EN60079

Afbeelding Illustration	Nominale stroom (A) Rated current (A)	Type
	0.5 A.	Z0804 - 0.5
	1 A.	Z0804 - 1
	1.25 A.	Z0804 - 1.25
	1.6 A.	Z0804 - 1.6
	2 A.	Z0804 - 2
	2.5 A.	Z0804 - 2.5
	3.15 A.	Z0804 - 3.15
	5 A.	Z0804 - 5
	6 A.	Z0804 - 6

Zekeringhouder Ex de Fuse holder Ex de

Technische informatie:

Ex markering: II 2 G Ex de IIC T4/T6 Gb

Geschikt voor zone 1 en 2

Aansluitingen: 10 mm²

Gewicht: 0,1 kg

Conform de standaards: EN60079

Technical data:

Ex mark: II 2 G Ex de IIC T4/T6 Gb

Can be used in zone 1 and 2

Connections: 10 mm²

Weight: 0.1 kg

Meets the standards: EN60079

Afbeelding Illustration	Omschrijving Description	Type
	Zekeringhouder Fuse holder	Z0509 6299
	2 A	Z0509 FR14G - 2 A
	4 A	Z0509 FR14G - 4 A
	6 A	Z0509 FR14G - 6 A
	10 A	Z0509 FR14G - 10 A
	16 A	Z0509 FR14G - 16 A
	20 A	Z0509 FR14G - 20 A
	25 A	Z0509 FR14G - 25 A
	32 A	Z0509 FR14G - 32 A
	40 A	Z0509 FR14G - 40 A